

NOTE: All items listed are paid for by MD-Kinney unless notated otherwise. Please order 3-4 weeks in advance to allow for production and shipping by 3rd party vendors.

6'x3' Vinyl Banner with Grommets

Customized heavy duty vinyl will withstand any shop environment. Grommets allow for easy hanging. Authorized Care Center and Authorized Distributor options available.

(MD-Kinney, M-D Pneumatics ONLY and Kinney ONLY brand variations available.)



24"x 12" Vehicle Magnet

24"x12" 30 mil. magnet to place on service vehicles.

(MD-Kinney, M-D Pneumatics ONLY and Kinney ONLY brand variations available.)



If you require assistance with a special size of magnet, contact the Branding Lead at kelsey.manlove@md-kinney.com.

SEND COMPLETED ORDER FORM TO: Kelsey Manlove | Branding Lead |

Factory Certified Repair Hang Tag

2-sided hang or shipping tag sized at 3.125"x6.25". Wire twist/tie included.

Attach to all repaired units being returned to end-user. Tags are customized with your service center contact information. Mailing address and phone number must be provided with order form submission. Channel Partner must have ASC (Authorized Service Center/Factory Certified Repair) designation/contract with MD-Kinney.

No minimum quantity required.

PERSONALIZATION EXAMPLE



SEND COMPLETED ORDER FORM TO: Kelsey Manlove | Branding Lead |

24"x36" Product Posters

1-sided, vertical, semi-gloss product posters. Ideal for hanging in entrances, show rooms service centers and trade shows.

(Custom / co-branded options not available for posters.)

Current Product Poster Visuals

M-D Pneumatics®

PD PLUS

Rotary Positive Displacement Blowers

HIGH PERFORMANCE & HEAVY DUTY DESIGN



PD Plus is known for quality, dependability, and outstanding performance.

- Models ranging from 3.25" to 1.2" gear diameter and 2.5" to 48" rotor length
- Ductile iron rotors and shafts
- Special materials offered
- Special testing available:
 - ASME PTC-9 (1 PSIG slip method)
 - Hydraulic testing to 150 PSIG (10.35 bar g)
 - Pressure gas testing to 100 PSIG (6.9 bar g)
 - Seal leakage testing
 - Noise testing
- Single and double envelope gas service available with mechanical seals

TYPICAL APPLICATIONS

- Pneumatic Conveying
- Steam Compression
- Mobile Vacuum Waste Removal
- Soil Vapor Extraction
- Process Gas Boosting
- Pulp & Paper Processing

M-D Pneumatics | www.md-kinney.com | (800) 825-6937

M-D Pneumatics®

CP SERIES

Rotary Positive Displacement Blowers

DEPENDABLE POWER & FLEXIBILITY



CP Series blowers are designed to be interchangeable with equivalent models of competing manufacturers.

- Standard features help reduce maintenance costs: sight glasses, triple lip seals, magnetic drain plugs
- Timed with precision helical gears, keyed to the rotor shafts
- Includes double-row ball bearing
- Rotors with integral shafts
- Reduced noise versions available with tri-lobe rotors
- Bi-directional rotation
- Rated up to 15 PSIG discharge pressure or 16 1/4" Hg dry vacuum

TYPICAL APPLICATIONS

- Pneumatic Conveying
- Carpet Cleaning
- Dairy Milking
- Air Sparging
- Wastewater Aeration
- Vacuum Excavation
- Dust Collection

M-D Pneumatics | www.md-kinney.com | (800) 825-6937

M-D Pneumatics®

EQUALIZER RM & DF

Rotary Positive Displacement Blowers

COMPACT & FLEXIBLE SOLUTIONS



Equalizer RM and DF blowers are designed to be interchangeable with equivalent models of competing manufacturers.

- Compact design
- Bi-directional rotation
- Timed with precision helical gears, keyed to the rotor shafts
- One piece housing
- Rotors with integral shafts
- Flow configuration is field convertible from horizontal to vertical
- Specific models available in popular 4.5" and 6" gear diameters

TYPICAL APPLICATIONS

- Pneumatic Conveying
- Dust Collection
- Carpet Cleaning
- Air Sparging
- Dairy Milking
- Compost Aeration

M-D Pneumatics | www.md-kinney.com | (800) 825-6937

M-D Pneumatics®

T855, T1055 & T855RS

Transport Rotary Positive Displacement Blowers

OUTPERFORM & OUTLAST THE COMPETITION



T855 and T1055 offer the largest oil sumps, providing you with better cooling than the competition.

- Longest bearing life
- Largest oil sumps = fewer oil changes
- Industry-leading IP69K breather
- Solid USA craftsmanship
- Built-in silencing chambers to reduce noise
- Smallest footprint in it's class
- 40 lbs lighter with improved quality design
- Versatility to unload a variety of dry bulk or granular materials
- Optional adaptor plate available
- Easily mount to existing vertical flow, L-shape brackets

T855 NOW EQUIPPED WITH RS ADVANCED TECHNOLOGY

The T855RS has a solvent painting coating applied to the rotor lobes which drastically reduces "slip". T855RS offers the most expansive range of flow than any blower in the transport market. Able to operate at lower speeds while moving more product than its predecessors, the T855RS can reduce offload times by as much as 25%, resulting in significantly reduced fuel consumption.

*Housing can track, stand on or dry vented housing (not with standard T855)

M-D Pneumatics | www.md-kinney.com | (800) 825-6937

KINNEY®

KVO

Rotary Vane Vacuum Pumps

COMPACT DESIGN & EASY MAINTENANCE



The KVO Series is an oil sealed, multi-vane, single-stage, air cooled, and direct-driven vacuum pump.

- Quick and easy replaceable filter elements to allow for premium oil filtration at a fast pace
- Equipped with automatic gas ballast valve to allow for trouble free water vapor handling
- Ultimate vacuum down to 0.375 Torr (with standard gas ballast) / 0.075 Torr (without gas ballast)
- Advanced cylinder and cover designs allow sound levels to be as low as 67 dB(A) for quiet operation
- Premium oil separator system ensures 99.997% of oil from the air stream is removed

TYPICAL APPLICATIONS

- Freeze Drying
- Vacuum Packaging
- Filling & Sealing
- Central Vacuum Systems
- Thermoforming
- Food Packaging
- Injection Molding

Kinney | www.md-kinney.com | (800) 825-6937

KINNEY®

KVC

Dry Claw Vacuum Pumps

HIGH EFFICIENCY & CONTACTLESS OPERATION



KVC dry claw pumps have a highly efficient design resulting in optimal CFM per HP.

- High-Efficiency NEMA framed motors included and are compatible with Variable Speed Drives
- No contaminants released into the discharge air or process with oil-free compression
- Dry compression process allows for premium performance without sealing fluids
- Ultimate Vacuum Down to 27" Hg (75 Torr)
- Sound levels as low as 76 dB(A)
- Fully synchronized gears ensure maximum efficiency in rotor movement
- Up to 20,000 hour maintenance intervals

TYPICAL APPLICATIONS

- Pick & Place
- CNC Router Tables
- Industrial Vacuum
- Central Vacuum Systems
- Thermoforming
- Food Packaging
- Degassification

Kinney | www.md-kinney.com | (800) 825-6937

KINNEY®

KLRC

Liquid Ring Vacuum Pumps

IDEALLY SUITED FOR PUMPING WET MIXTURES



Complete engineered system solutions are available for solvent recovery, increased performance, and monitoring through instrumentation, controls, piping, and valves.

- Non-sparking vacuum pump removes gases through the use of rotating impeller blades that water and have a ring of liquid
- Impellers axially locked to shaft to maintain clearances at both ends, ensuring no shaft skew or spacer to machine
- Center-actuated for easy draw access to either end of the pump without total disassembly for faster and easier repairs
- Clearance maintained by bearing spacers, makes easy and quick re-assembly
- Two-stage design
- Capacity: 75 - 950 CFM (128 - 1615 M3/hr)
- Maximum vacuum: 29" Hg Vac (23 mmHg Absolute)

TYPICAL APPLICATIONS

- Chemical Processing
- Pharmaceutical Processing
- Vapor Recovery
- Dewatering
- Extruders
- Crystallizers

Kinney | www.md-kinney.com | (800) 825-6937

KINNEY®

A SERIES

Liquid Ring Vacuum Pumps

SIMPLISTIC DESIGN & RUGGED CONSTRUCTION



- Flat power curve over entire vacuum range prevents motor overload
- Reduced stress on motor shaft and bearings
- Increased water handling capability prevents heat build-up, extends life of mechanical seals
- Compact, close-coupled design eliminates need for interstate manifold or motor alignment
- Single-stage design
- Vibration Free
- Capacity: 10 - 300 CFM (17 - 510 M3/hr)
- Maximum Vacuum: 28.3" Hg Vac (40 mmHg Absolute)

TYPICAL APPLICATIONS

- Solvent Distillation
- Gas Compression
- Extruders
- Sterilization
- Evaporators
- Degassifiers

Kinney | www.md-kinney.com | (800) 825-6937

SEND COMPLETED ORDER FORM TO: Kelsey Manlove | Branding Lead |

Retractable & Custom Banners | Standard & Co-branded

MD-Kinney offers standard and customized product banners for use at trade shows, show rooms and general marketing efforts. Please send an email to the MD-Kinney Branding Lead and CC your Regional Sales Manager to set up a brief meeting to further discuss usage and banner design. All MD-Kinney provided banners will showcase the MD-Kinney as the prominent brand and message.

(Banner requests must be submitted 4-6 weeks prior to usage / trade show needs to allow for production. Rush projects for custom banner designs submitted under 4 weeks will not be accepted.)



SEND COMPLETED ORDER FORM TO: Kelsey Manlove | Branding Lead |

MARKETING & PROMOTIONAL ITEM ORDER FORM

Channel Partner Company Name:			
Contact Name:			
Email:		Phone:	
Shipping Address:			
City:	State:	Zip Code:	
Branding Desired:	MD-Kinney (Vacuum & Blower)	Kinney (Vacuum Only)	M-D Pneumatics (Blower Only)
Proof Request:	ASC (Only)	Distributor (Only)	ASC & Distributor

6x3 Vinyl Banner with Grommets	Quantity:	(Max Order of 2)
Mailing Address (required):		
Company Phone (required):		
Website (required):		

24"x12" Vehicle Magnet	Quantity:	(Max Order of 10)
-------------------------------	-----------	-------------------

Factory Certified Repair Hang Tags	Quantity:	(Max Order of 250)
Mailing Address (required):		
Company Phone (required):		

24"x36" Product Posters (no co-branding available)	Quantity (each):	(Max Order of 2 Each)	
PD Plus (Blower)	CP Series (Blower)	Equalizer (Blower)	T855/T1055/T855RS/ (Transport)
KVO Vane (Vacuum)	KVC Dry Claw (Vacuum)	KLRC Liquid Ring (Vacuum)	A Series Liquid Ring (Vacuum)

Special Requests (additional inclusion of websites/phone numbers/logos/ect...)

Please provide your company logo via email when submitting your request.

SEND COMPLETED ORDER FORM TO: Kelsey Manlove | Branding Lead |